DNV Id.NO.: I6p10039 Report No:PUN/16/NT/562 Date:14/10/2016



TYPE TEST CERTIFICATE OF

FLUID CONTROLS PVT. LTD.

OFFICE: J.V.PATEL, ITI COMPOUND, B. MADHURKAR MARG, MUMBAI – 400 013, INDIA. **FACTORY**: T-169, MIDC, BHOSARI, PUNE – 411 026, INDIA.

The under mentioned surveyor did visit the facilities of the above manufacturer of metallic tube connections(Single ferrule fittings), between 1st April 2016 to 22nd September 2016 for the performance appraisal of tests mentioned below and conducted on under mentioned sizes of fittings as per mentioned norms.

Material Grade of Fittings: Stainless Steel ASTM A276 TP SS 304 or equivalent. Material Grade of Tube : Stainless Steel ASTM A269 TP SS 316 Seamless.

1. Test Parameters used:

- a. Temperature during testing: Ambient ($25\pm10^{\circ}$ C).
- b. Test pressure retained within $\pm 5\%$ PSIG.
- c. Test medium demineralised water/SAE grade 10W oil for hydraulic tests.
- d. Metallurgical tests done at NABL approved laboratory.

2. Size of mechanically attached fittings with respect to Tube OD x Wall Thickness (WT)):

3. Following tests are conducted as per below mentioned standards and witnessed along with review of relevant documents.

Size	
10 MM OD x 1.5 MM WT	
18 MM OD x 2.0 MM WT	
22 MM OD x 2.0 MM WT	
42 MM OD x 3.0 MM WT	

Test	Standard
Repeated Assembly Test	ISO 19879
Leakage Test	ISO 19879
Proof Test	ISO 19879
Burst Test	ISO 19879
Cyclic Endurance Test	ISO 19879
Vaccum Test	ISO 19879
Overtightning Test	ISO 19879
Vibration Test	ISO 19879
Cyclic endurance (impulse) Test with Vibration	ISO 19879
Pull out test	IACS P2.11:2001
Salt Mist Test	IEC 60068-2-52

All the above tests have been found satisfactory. The details of the applicable test pressures with reference to various tests mentioned above have been witnessed and attested by DNV in the report of the manufacturer.

The above mentioned fittings meet the requirement of above mentioned standards with reference to the tests which mentioned in the specification and conducted herein.



Naresh Turerao
Surveyor of DET NORSKE VERITAS AS

If any person suffigs loss or damage which is proved to have been caused by any negligent act or omission of Det Norske Veritas, then Det Norske Veritas shall pay compensation to such person for his proved direct loss or damage. However, the compensation shall not exceed an amount equal to ten times the fee charged for the service in question, provided that the maximum compensation shall never exceed USD 2 million. In this provision "Det Norske Veritas" shall mean the Foundation Det Norske Veritas as well as all its subsidiaries, directors, officers, employees, agents and any other acting on behalf of Det Norske Veritas.

DET NORSKE VERITAS AS, VERITASVEIEN 1, N-1322 HØVIK, NORWAY TEL.INT: +47 67 57 99 00, TELEFAX: +47 67 57 99 11

Form No.: 40.91a Issue: January 98

Page 1 of 1